

**PRODUCT DESCRIPTION**

AWP™ Acrylic Primer is used as a primer, sealer and bonding agent to prepare floor surfaces prior to the application of the waterproofing membrane and wall coating system.

**PRODUCT FEATURES**

- Easy to mix, only add water
- Increase adhesion between substrate and waterproofing material
- If used as a sealant supplement, it reduces the consumption of sealant.
- Acrylic coating has high adhesion to a variety of materials.
- Very suitable alternative to old sealing systems and the ability to reduce the weight of the structure
- High flexibility
- Applicable on horizontal and vertical surfaces

**PRODUCT USES**

- Reduce dust and increase bonding of the substrate.
- Act as a bonding agent to old floors.
- Prime and use as a bonding agent on smooth concrete finishes.
- Seal pores on rough porous concrete to eliminate air bubbles.
- As a primer on bitumen membrane prior to the application of Sovacryl.

**TECHNICAL DATA**

Specific gravity	1.01Kg/L
Coverage	8 - 10 m2 per litre
Flash point	Non-flammable
Drying time	30 min
Mixing Ratio	1 part liquid 1 part water

**SURFACE PREPARATION**

- Ensure that the surface is dry, clean and free from curing compound or release agents.
- No chipping or roughening of surface is required if the condition is stable. Old paint work which is stable can remain.
- Any contamination, including commercial detergents used for cleaning, must be thoroughly rinsed off with plenty of water

**APPLICATION**

- The surface for bonding treatment must be thoroughly cleaned of all laitance, loose material, oil, greases etc.
- Pre-wet the surface with water adequately to saturate surface dry condition. Ensure that there is no standing water
- After saturating the surface apply 1-2 coat of primer with brush mixed with water in 1:1 ratio
- Allow the primer to dry for 30-60 mins depending upon weather conditions

**PACKAGING**

Acrylic Primer AWP™ is available in 20 liter containers.



Acrylic Based Waterproofing Primer - AWP™

**SHELF LIFE**

Shelf life of up to 12 months from the date of manufacture. Store in a cool place away from direct sunlight. Avoid freezing of the Primer.

**HEALTH AND SAFETY**

AWP™ may cause skin irritation and sensitization. Use of chemical resistant gloves is recommended. Avoid breathing vapors and dust. Get medical attention if you are breathing with difficulty. Resins products can cause strong eye irritation. Avoiding eye contact and Using safety goggles is necessary. In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with plenty of water; contact physician immediately. For respiratory problems, remove to fresh air. Wash clothing before reuse.

**DISCLAIMER OF LIABILITY**

Buyer determines suitability of product for use and assumes all risks. Buyer's sole remedy shall be limited to replacement of product within one month. Any claim for breach of this warranty must be brought within one month of the date of purchase. AFZIR shall not be liable for any consequential or special damages of any kind, resulting from any claim or breach of warranty, breach of contract, negligence or any legal theory.

The Buyer, by accepting the products described herein, agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production.